

MULTI PRO

PAINT PROTECTION FILM

TRANSPARENT | GLOSS

PRODUCT DESCRIPTION

MULTI PRO is a transparent, adhesive-coated TPU paint protection film that heals itself at ambient temperature. It is made to protect the original paint of a car. Its shock-absorbing structure helps protect the bodywork against chips caused by stones, insects, car doors, car-wash brushes and similar impacts. The surface finish is gloss and the film keeps dirt from sticking, which makes the car easier to clean.

FILM FEATURES

Property	Value
Material	Transparent TPU film with adhesive coating
Thickness available	180 µm, 195 µm or 210 µm
Roll width	1520 mm
Roll length	15 m
Surface finish	Gloss
Self-healing	At ambient temperature, without added heat

LINER

- ◆ Silicone-coated PET liner.

ADHESIVE

- ◆ Transparent, solvent-based acrylic adhesive.
- ◆ Immediate adhesion that reaches its best strength after 24 hours of contact with the paint.

USER'S INSTRUCTIONS

- ◆ Wet application method.
- ◆ Recommended minimum application temperature: +10 °C (+50 °F). Apply preferably between +15 °C and +35 °C (+59 °F and +95 °F).
- ◆ Cut the film to the size of the part to be covered, leaving about 10 cm (4 in.) of extra margin on every side.
- ◆ Apply only to clean surfaces free of dust, grease, wax and silicone. Take extra care to clean angles and edges, so the film can grip the whole outline of the part.
- ◆ Apply only to undamaged original paintwork. If the paint is not original or is damaged, applying and removing the film is at the installer's judgement and risk.
- ◆ Self-healing: light scratches in the surface of the film fade by themselves at ambient temperature. The effect is quicker in warm weather.

OPERATING RECOMMENDATIONS

- ◆ A conformable film for protecting bodywork, painted bumpers, rear-view mirror casings and other exposed areas against chips from stones and insects, and against light scratches.
- ◆ Useful protection against minor vandalism such as scuffs.
- ◆ To make application easier, use squeegees from soft to hard (plastic or felt-edged) according to the shape of the part.
- ◆ For the application method step by step, see the MULTI PRO application guide at multipro.protectionhousegroup.com.

STORAGE

Keep the remaining film on its original core. Do not cut the roll into shorter lengths or widths, and do not repackage it. Close the roll straight after use, with masking tape or roll collars, to keep the film in good condition.

Condition	Recommendation
Storage area	Dust-free, dry environment
Storage temperature	+15 °C to +25 °C (+59 °F to +77 °F)
Relative humidity	About 50 %
Packaging	Keep the roll in its original packaging until use
Orientation of rolls	Vertical (upright)
Heat	Keep away from radiators, heaters and direct sunlight

CARE OF THE INSTALLED FILM

- ◆ Do not wash the vehicle during the first 48 hours after installation.
- ◆ Wash with a pH-neutral car shampoo and a soft cloth or sponge.
- ◆ Do not use solvents, abrasive polishes or corrosive cleaners.
- ◆ If you use a pressure washer, keep the nozzle at least 50 cm (20 in.) from the film, use medium pressure and water no hotter than 35 °C (95 °F).

Notes. Substrates and applications vary a lot, so the installer must check that the film suits each application before installing it. If in doubt, test on a small, hidden area first. The information in this sheet is given in good faith and is not a binding guarantee. The seller is not liable for indirect damage, and its liability is limited to the replacement value of the film bought. Specifications may change without notice. The latest version is always on multipro.protectionhousegroup.com.



Protection House
multipro.protectionhousegroup.com
WhatsApp: wa.me/message/5DYJ3COOANTVF1